

Screw terminal black, 10mm² (EM153)

To connect conductors in connection sockets, junction boxes, canopies or renovation sockets.


Tested according to EN 60998.



Master data

Item number	904941
Type	EM153 2,5-10
Description 1	Screw terminal
Brand	DQ
Dimension	12 x 2,5-10mm ²
Colour	Black
Material	Polypropylene
PU1	10
Unit of quantity	Piece
Weight	4.12 kg
Weight unit	kg/100 pc.

Dimensions



Length	134 mm
Width	23 mm
Height	17 mm

The worker's choice



Screw terminal black, 10mm² (EM153)

Technical data

Closing plate required	no
Connectable conductor cross-section, single-wire, max.	10 mm ²
Connectable conductor cross-section, single-wire, min.	2.5 mm ²
Connectable conductor cross-section, fine-wire without wire-end ferrule, max.	6 mm ²
Connectable conductor cross-section, fine-wire without wire-end ferrule, min.	2.5 mm ²
Connectable conductor cross-section, multi-wire, max.	6 mm ²
Connectable conductor cross-section, multi-wire, min.	2.5 mm ²
Connection position	Side
No. of terminals	12
Number of screwless terminals per pole	2
Version of electrical connection 1	Screw connection
Version of electrical connection 2	Screw connection
Drill hole spacing, centre	11.5 mm
Explosion-tested version	no
Suitable for flexible conductors	yes
Suitable for solid conductors	yes
Suitable for multi-wire conductors	yes
Halogen-free	yes
Mounting type	Direct mounting
Nominal cross-section, max.	10 mm ²
Nominal cross-section, min.	2.5 mm ²
Nominal voltage	450 V
Nominal current	10 A
Pole number	12
Screw tightening torque	0.8 Nm
Permitted temperature range, max.	80 °C
Permitted temperature range, min.	-5 °C
Transparent	no
Ambient temperature	80 °C