

Screw anchor (MZ123)



For direct installation of e.g. spacer clips or cable clamps out of metal without dowels in cracked and non-cracked concrete and masonry.

European Technical Assessment, including characteristic values under fire exposure to fire resistance R 120 for use in functional integrity in accordance with DIN 4102-12.

ETA-15/0784: Mechanical fasteners for use in concrete

ETA-15/0785: Fasteners for use in concrete for redundant non-structural systems

ETA-20/0132: Screw anchor for use in masonry



Master data

Item number	950128
Type	MZ123 6x40
Description 1	Screw anchor
Brand	DQ
Dimension	6,0x40mm
Material	Steel
Surface	Electrogalvanized
Surface standard	EN ISO 19598 / EN ISO 4042
PU1	100
Unit of quantity	Piece
Weight	0.908 kg
Weight unit	kg/100 pc.

Dimensions



Dimension	6 x 40
Length	40 mm



The worker's choice



Screw anchor (MZ123)

Technical data

Drill hole depth	40 mm
Drill hole diameter, min.	5 mm
Hardened	yes
Thread diameter ST	6
Head diameter	11.2 mm
Head shape	Cup head
Screw system	Torx
Effective anchoring depth	35 mm
Fireproof	yes
Fire resistance class EN 13501-1	R30 R60 R90 R120
Suitable for cracked concrete	Yes
Suitable for uncracked concrete	Yes
Size TX (Torx)	30