

Universal cable support Kabel-Fixx



Characteristics

- **Material** PA 6.6, UV-resistant, halogenfree
- **Colour** black
- **Flame-resistant** UL 94V-2
- **Application temperature** -40 °C to +85 °C
- **Tensile strength** At 23 °C: 844 kg/cm² acc. ASTM D-638
- **Further specification** ASTM-D4066 PA181
- **Diameter hole** 3,5mm
- **Toothing** Internal and External, releaseable only External

Kabel-Fixx

The Kabel-Fixx – universal, easy, fastening without further tools

Type	Closure	Length mm	Max. Bundle-Ø mm	Width mm	Min. holding force [N]	Content [piece] in bag	VPE	Item No.
OZ091 10x200	Plastic lip	200	50	10	220	100	20	905210
OZ091 10x280	Plastic lip	280	75	10	220	100	20	905213
OZ091 10x385	Plastic lip	385	100	10	220	100	20	905216
OZ091 10x200 S	Plastic lip, tensile strengthened	200	50	10	450	100	20	905212
OZ091 10x280 S	Plastic lip, tensile strengthened	280	75	10	450	100	20	905215
OZ091 10x385 S	Plastic lip, tensile strengthened	385	100	10	450	100	20	905218
OZ091 10x200 R	Pastic lip, releaseable	200	50	10	220	100	20	905211
OZ091 10x280 R	Pastic lip, releaseable	280	75	10	220	100	20	905214
OZ091 10x385 R	Pastic lip, releaseable	385	100	10	220	100	20	905217