


## Push-in dowel



### Characteristics

- |   |   |
|---|---|
| • <b>Material</b>                                     | Polyamide 6.6   |
| • <b>Colour</b>                                       | Grey, RAL 7035  |
| • <b>Operation Temperature</b>                        | -20 °C up to + 85 °C  |
| • <b>Max. Load</b><br>(tested with OPDZ<br>20mm pipe) | 298 N in Concrete<br>268 N in Solid brick<br>274 N in Hollow brick<br>131 N in Cellular concrete<br>197 N in Plasterboard |

### Application:

The proven method to easily mount a Snap-On pipe clamp by hand.

### All Advantages at a Glance

- Quick and easy to mount by hand on walls or ceilings, without use of tools.
- Drill a 6 mm. hole and simply insert the dowel by hand.
- The Push-in dowel combines plug and screw and is a time saving application, no screwing needed.
- A Snap-On pipe clamp can be clicked on the push-in dowel before or after mounting.
- Easy releasable, simply turning it out of the hole.

### Push-in dowel (PG045/PG046)

Type	Push-in depth	Contents PU pcs	Weight per PU kg	Shipping Box PU	GTIN	Item No.
<b>PG045 AM25</b>	25 mm	100	0,231	10	8713678052005	<b>905200</b>
<b>PG046 AM50</b>	50 mm	100	0,231	10	8713678052012	<b>905201</b>

