

Universal Wire Connector



Characteristics

• Insert	Copper
• Spring	Stainless steel
• Cover	Polycarbonat
• Colour	White
• Number of terminals	3 – 5
• Nominal voltage	450 V
• Nominal current	24 A
• Ambient temperature	Max. +120 °C
• Wire skinning length	9 – 10 mm
• CE according	EN 60998-1/2:2004/60998-2-1:2004

Application:

With our Universal wire connector you can easily connect electrical devices. They are mostly used in areas with permanent electrical connections.

All Advantages at a Glance

- Clamping range: 0.2 mm² – 2.5 mm² for solid, rigid stranded and flexible wires.
- A number of wire cross sections can be combined in one terminal.
- High pull-out forces.
- Connection of rigid wires without activating the release lever.
- Viewing window for visual inspection of the clamping points means greater safety during installation.

Universal Wire Connector (EM034)

Type	# of poles	Contents PU pcs	Weight per PU kg	Shipping Box PU	GTIN	Item No.
EM034 2	2	100	0,2	20	8713678003410	900341
EM034 3	3	75	0,19875	20	8713678003427	900342
EM034 5	5	50	0,2075	20	8713678003434	900343



Don Quichotte B.V.

P.O. Box 60, 5700 AB Helmond
Industrial Zone 9081
Gerstdijk 17, 5704 RG Helmond
The Netherlands

Tel.: +31 492 74 50 00
Fax: +31 492 74 50 99
info@don-quichotte.com
www.don-quichotte.com