


Insulation Dowel INSU-Fixx



Characteristics

Load range	From 3 to 5 kg
Suitable board	60 mm insulation board
Drive dowel	Torx 40
Length dowel	63,5 mm
Dimension head	Ø 25 mm x 1,5 mm
Material	Polyamide (PA)
Diameter screw usage	Ø 3,5 – 5 mm
Max. drilling depth	50 mm

Application

To be used to anchor light-weight components through outside plaster directly in solid insulation materials. Easily mounted without need of pre drilling due self-tapping thread and special point geometry.

This way you can install letter boxes, outside lights or house numbers without using other tools through the outside plaster directly into the isolation, avoiding thermal bridges.

To prevent water from penetrating a EPDM rubber washer (Ø 23 mm x 2,5 mm) can be used to seal the plug collar. Before installing the insulation dowel place the rubber washer over the dowel point.

Insulation Dowel INSU-Fixx

Type	Description	Dimension mm	Colour	Content pcs	Weight per PU kg	GTIN	Item No.
PG050	Dowel	9 x 63,5	Natural	50	0,295	8713678005209	900520
PG051	Rubber washer	23 x 2,5	Black	50	0,0447	8713678005223	900522
PG052	Dowel + washer set	9 x 63,5	Natural/Black	50	0,3397	8713678005186	900518

Don Quichotte B.V.

P.O. Box 60, 5700 AB Helmond
Industrial Zone 9081
Gerstdijk 17, 5704 RG Helmond
The Netherlands

Tel.: +31 492 74 50 00
Fax: +31 492 74 50 99
info@don-quichotte.com
www.don-quichotte.com